



Questionnaire Gears

Web www.giebel-adsorber.de or E-Mail info@giebel-adsorber.de

Contact

Company:

Telephone:

.....

.....

Contact person:

E-Mail:

.....

.....

Description / Project reference:

.....

.....

.....

Requirement:

Required quantity:

Ventilation drying (Drying the supply air)

.....

Oil mist separator (Cleaning the air)

(just) Water drop deposition

Transmission data

Transmission volume:

[Oil- and air volume]:

Gear oil:

0 – 5 l

biodegradable oil

Mineral oil

5 – 10 l

flame retardant oil

other:

10 – 50 l

.....

50 – 100 l

100 – 800 l

Oil-temperature:

Location:

800 – 2400

> 60 °C

Outside use

2400 - l

< 60 °C

Indoor use



Commitment / Setting:

Environment moist [% rF]:

- dry (0-50 % rF)
- normal (50-70 % rF)
- damp (70-100 % rF)

Setting:

- normal
- ATEX2014 (Ex-Zone)
- corrosive (Offshore, Marine on deck)

Material requirement:

- no, plastic
- yes, Aluminum
- yes, Stainless steel A4

Ambient air:

- cold (<10 °C)
- normal (10-30 °C)
- warm (>30 °C)

Use conditions:

- Stationary
- Mobile

Heavily dusty air:

- yes
- no

Handing / Operation:

- simple (disposable)
- cheap (refillable)

Screw threads:

- Inner thread:
- External thread:
- other: